AL600ULXB
Off-line Switching Power Supply/Charger

Rev. DSAL600ULXB_04162012

AL600ULXB

Overview

AL600ULXB is a UL Recognized power supply/charger which converts a 115VAC, 60Hz input into a single 12VDC or 24VDC non-power limited output.

Specifications

Input:
- Input 115VAC, 60Hz, 1.9 amp.

Output:
- 12VDC or 24VDC selectable output.
- 6 amp continuous supply current.
- Filtered and electronically regulated output.
- Short circuit and thermal overload protection.

Battery Backup:
- Built-in charger for sealed lead acid or gel type batteries.
- Automatic switch over to stand-by battery when AC fails.
- Maximum charge current 0.7 amp.

Supervision:
- AC fail supervision (form “C” contacts).
- Low battery supervision (form “C” contacts).
- Battery presence supervision (form “C” contacts).

Visual Indicators:
- AC input and DC output LED indicators.

Electrical:
- Operating temperature: 0º C to 49º C ambient.
- 27-55 BTU/Hr.
- System AC input VA requirement: 218.5VA.

Mechanical:
- Product weight (approx.): 1.55 lbs. (0.70 kg.).
- Shipping weight (approx.): 1.75 lbs. (0.79 kg.).

Agency Approvals

UL Recognized component for Access Control System Units (UL 294), Standard for Safety for Fire Protective Signaling Systems (UL 1481).

Board Dimensions *(L x W x H) (approximate)*:

4.5” (114.3mm) x 7.11” (180.59mm) x 2.01” (51.05mm)